

# MODEL 5441

## Diazo Duplicator

CROWLEY

- A great medium-duty duplicator with convenient operator controls
- High resolution and uniform density at a low price
- Quality construction and digital temperature controls for outstanding durability
- In use by government agencies, private organizations and service bureaus worldwide.

### FEATURES

- 0 to 80' per minute; average masters using black diazo process between 40 and 50 FPM
- Closed-Loop aqueous system permits safe and odorless operation in an office environment
- Operator convenience and safety features provide protection from stray ultraviolet light
- Film cleaner Model TR129 (optional)
- Bi-directional rewind system and optional work table (optional)
- Universal fittings for convenient use of commercially-available ammonia and absorber
- Will duplicate up to 200 rolls of film per day; 16mm/35mm

### EASY TO USE CONTROL PANEL

International symbols are used.

### SELF-THREADING SYSTEM

Slide master film into the convenient guide slot and the Extek 5441 does the film threading through the expose area

### OPTIONAL FAST-REWIND CAPABILITY

The Extek 5441 can accommodate all types of reels and is designed to rewind your film master onto the original reel at speeds up to 1,000 fpm



extek  
Microsystems

### GENERAL SPECIFICATIONS

**Film Size:** 16/35mm

**Film Type:** All available Diazo materials

**Film Roll Diameter:** 9.5"; (241mm) maximum

**Film supply Master & Duplicate:** 200'; 615 meters (2.4 mil)

**Machine Speed:** Variable, up to 80 fpm (24mpm)

**Resolution:** 180 lines/mm minimum

**Developer:** 20 to 24 Baume aqueous ammonia

**Absorber system:** 2.5 gal (9.51) reservoir

**Venting:** Not required

**Electrical:** 115 Vac, 60 Hz, 13A maximum

**Environmental:** 60° to 80°F (16° to 26°C)

**Operating:** 40% to 70%RH, - 40° to 140°F

**Storage:** (-40° to 60°C)

**Weight:** Table-top unit: 150 lbs (68 kg)

Shipped (crated): 240 lbs (109 kg)

*Specifications subject to change without notice*